

WATER TREATMENT & DRILLING CHEMICAL (Oil & Gas)

- ⦿ Hydrochloric Acid (HCL) 34-36 %
- ⦿ Sulphuric Acid 98%
- ⦿ Nitric Acid 61% / 68%
- ⦿ Poly Aluminium Chloride (PAC)
- ⦿ Poly DADMAC
- ⦿ Calcium Hypochlorite 65%
- ⦿ Aluminium Chlorohydrate (ACH)
- ⦿ PVD Salt
- ⦿ Table/Common Salt
- ⦿ Raw Salt
- ⦿ Ferric Chloride (Anhydrous / Liquid)
- ⦿ Ferrous Sulphate Heptahydrate
- ⦿ Aluminium Sulphate
- ⦿ Hydrogen Peroxide (H₂O₂) 35% / 50%
- ⦿ Hydrated Lime 70–75% / 90–92% / 94–96%
- ⦿ Tablet Salt
- ⦿ Crystal/Powder Salt
- ⦿ Refined Salt
- ⦿ Common Salt
- ⦿ Iodized Salt
- ⦿ Silicon Emulsion

- ⦿ Bentonite Powder (OCMA / API / Feed Grade)
- ⦿ Guar Gum
- ⦿ Xanthan Gum
- ⦿ Formic Acid
- ⦿ Acetic Acid
- ⦿ Demulsifier
- ⦿ Sodium Sulfite
- ⦿ Polyacrylamide
- ⦿ Calcium Chloride
- ⦿ Calcium Bromide Solution 52%
- ⦿ Hydro Bromic Acid Solution 48%
- ⦿ Silicon Based Defoamers
- ⦿ Mineral Oil Based Defoamers
- ⦿ Non-Silicon Defoamers
- ⦿ Glycol Based Defoamers
- ⦿ Alcohol Based Defoamers
- ⦿ Food Grade Defoamers
- ⦿ Fatty Acid Based Defoamers
- ⦿ Water Based Defoamers
- ⦿ Powder Defoamers
- ⦿ Polymeric Defoamers

OUR CERTIFICATIONS

